## Call Points

# CP-31/34 Series

### Reliable, Flexible, Conventional



CP-31/34 Series with Plastic Glass





ANXELL CP-31/34 series call point is a conventional call point that offers double pole, triple pole, or quadruple pole changeover contacts with normally open and closed connections. It is supplied with a breakable plastic glass element that produces no glass fragments to ensure safe and reliable operation. Available in various colors for your choice.

#### **Standard Features & Specifications**

• Operating voltage: 12~24 VDC

• Plastic glass operating element

• Contact resistance:  $100m\Omega$ 

 Contact rating: 5A 125/250 VAC (for CP-31 series) 1A/125VAC (for CP-34 series)

• Test key included

Available in various colors (Green/Yellow/White/Red/Blue)

## **CP-34GPBZ-LB Special Features**

- 12 or 24 VDC input terminal
- Built-in 80dB buzzer
- Blue/Red & Blue/Green backlight illuminations

#### Patents, Approvals, and Listings


• CE: 332113

### **CP-31/34 Series Call Points**

| Models                                  | Contact        | Breakable<br>Plastic Glass | Built-in<br>Buzzer | 12/24 VDC<br>Input<br>Terminal | Blue/Red &<br>Blue/Green<br>Backlight | Case Colors                     |
|---|----------------|----------------------------|--------------------|--------------------------------|---------------------------------------|---------------------------------|
| CP-31 <u>G</u> P<br>CP-31 <u>G</u> P-UC | Double pole    | •                          | _                  | _                              | _                                     | Green, Red, Yellow, White, Blue |
| CP-34 <u>G</u> P<br>CP-34 <u>G</u> P-UC | Quadruple pole | •                          | _                  | _                              | _                                     | Green, Red, Yellow, White       |
| CP-34GPBZ-LB<br>CP-34GPBZ-LB-UC         | Triple pole    | •                          | •                  | •                              | •                                     | Green, Red, Yellow, White       |

<sup>\*</sup> Models with UC suffix in the model number include a clear plastic cover.

#### **Dimensions**



All dimensions in mm

#### **Accessories**



CP-31-PL
Plastic Glass Element
4 pcs in a pack



CP-31-UC Clear Plastic Cover




P-PL-CP-31-K Test Key


### Wiring for CP-31/34 Series Call Points


The CP-31/34 series uses terminal block connectors and wiring to the relevant terminal blocks provides normally open or normally closed operation. When the plastic element is broken, the internal switches will change from NC to NO operation, triggering the connected devices.





#### **CP-34 Series Wiring Diagram**





### **Blue/Green/Red Backlight Illumination (For CP-34GPBZ-LB)**

The CP-34GPBZ-LB features backlight illumination that changes from blue to red or green after the plastic glass element is broken.



#### Warranty

The product is warranted against defects in material and workmanship while used in normal service for a period of 1 year from the date of sale to the original client. The ANXELL policy is one of continual development and improvement; therefore ANXELL reserves the right to change specifications without notice.

